

In Re Patent Application of:
AHMED
Serial No. 10/606,080
Filing Date: June 25, 2003

In the Claims:

1-20 (Canceled).

21. (Previously presented) A method for transmitting an input wave comprising the steps of:

generating two or more signals that represent said input wave when combined;

modulating a carrier wave with at least one characteristic of at least one of said two or more signals to generate a modulated signal;

modulating a phase shifted carrier wave with a characteristic of another of said two or more signals to generate a phase shifted modulated signal;

inputting said modulated signal and said phase shifted modulated signal into an amplifier having at least two amplifying segments;

controlling at least one of said amplifying segments with a digital control signal containing a characteristic of one of said two or more signals that represent said input wave when combined to generate at least one segment output;

controlling at least another of said amplifying segments with another digital control signal containing a characteristic of another of said two or more digital signals that represent said input wave when combined to generate at least one other segment output;

transmitting an output signal based upon said at least one segment output and said at least one other segment

In Re Patent Application of:
AHMED
Serial No. 10/606,080
Filing Date: June 25, 2003

output.

22. (Original) The method of claim 21, wherein said two or more signals comprise an in-phase and a quadrature signal.

23. (Original) The method of claim 21, wherein said characteristic used to generate said digital control signals is magnitude.

24. (Original) The method of claim 21, wherein said characteristic used to modulate said carrier wave is sign.

25. (Previously presented) The method of claim 22, wherein said carrier wave is a radio frequency (RF) signal.

26. (Previously presented) The method of claim 22, wherein said at least one segment amplifies power.

27. (Previously presented) The method of claim 22, wherein said at least one segment is a current source.

28. (Previously presented) An apparatus for electromagnetic processing of an input wave comprising:
an amplifier having at least two amplifying segments for receiving a modified signal derived from two or more signals that represent said input wave when combined; and
a control circuit for regulating said modified signal across one amplifying segment using a digital signal

In Re Patent Application of:
AHMED
Serial No. 10/606,080
Filing Date: June 25, 2003

containing a characteristic of one of said two or more signals, and for regulating said modified signal across another of said amplifying segments using another digital signal containing a characteristic of another of said two or more signals.

29. (Original) An apparatus as in claim 28, wherein said two or more signals are in quadrature with each other.

30. (Original) An apparatus as in claim 28, wherein said characteristic used to regulate said modified signal is magnitude.

31. (Previously presented) An apparatus as in claim 28, further comprising an output circuit for generating an output signal from said regulating of said modified signal.

32. (Original) An apparatus as in claim 28, wherein one or more of said segments comprises a power amplifier.

33. (Previously presented) An apparatus as in claim 32, further comprising a combining circuit for combining an output from one or more of said segments, wherein said combining circuit comprises one or more selected from the group consisting of power transformers, quarter-wave transmission lines, discrete LC components, and Pi-networks.

34. (Previously presented) An apparatus as in claim 28, wherein one or more of said segments is a current source

In Re Patent Application of:
AHMED
Serial No. 10/606,080
Filing Date: June 25, 2003

that contributes current to the output signal.

35. (Original) An apparatus as in claim 28, wherein said received modified signal contains only one of said two or more signals used to derive said modified signal.

36. (Original) An apparatus as in claim 28, further comprising:

a source of a carrier wave;
a phase shifter for phase shifting said carrier wave to generate a phase shifted carrier wave;

a mixer for mixing a characteristic of one of said two or more signals that represent said input wave when combined with said carrier wave; and

another mixer for mixing a characteristic of another of said two or more signals that represent said input wave when combined with said phase shifted carrier wave.

37. (Previously presented) An apparatus as in claim 36, wherein said carrier wave is a radio frequency (RF) signal.

38. (Original) An apparatus as in claim 36, wherein said carrier wave and said phase shifted carrier wave have a relative phase difference of 90° .

39. (Original) An apparatus as in claim 28, further comprising a signal generator for generating said two or more

In Re Patent Application of:
AHMED
Serial No. 10/606,080
Filing Date: June 25, 2003.

signals that represent said input wave when combined.

40. (Original) An apparatus as in claim 39, further comprising a signal processor for processing one or more of said two or more signals that represent said input wave when combined.

41. (Original) An apparatus as in claim 40, wherein said signal processor is programmed to do one or more selected from the group consisting of performing correction of an amplitude characteristic of a carrier wave used in said derivation of said modified signal, correction of a phase characteristic of a carrier wave used in said derivation of said modified signal, and filtering of one or more of said two or more signals that represent said input wave when combined.

42. (Previously presented) An apparatus for transmitting an input wave comprising:

a signal generator for generating two or more signals that represent said input wave when combined;

a signal modulator for modulating a carrier wave with a characteristic of at least one of said two or more signals to generate a modulated signal and for modulating a phase shifted carrier wave with a characteristic of another of said two or more signals to generate a phase shifted modulated signal;

an amplifier having at least one amplifying segment for receiving said modulated signal and at least one other

In Re Patent Application of:
AHMED
Serial No. 10/606,080
Filing Date: June 25, 2003

amplifying segment for receiving said phase shifted modulated signal;

a controller for controlling said at least one amplifying segment with a digital signal containing a characteristic of one of said two or more signals and for controlling said at least one other amplifying segment with another digital signal containing a characteristic of another of said two or more signals to generate at least one segment output; and

an output circuit for transmitting an output signal based upon said at least one output segment.

43. (Original) The apparatus of claim 42, wherein said two or more signals comprise an in-phase and a quadrature signal.

44. (Original) The apparatus of claim 42, wherein said characteristic used to generate said control signal is magnitude.

45. (Original) The apparatus of claim 42, wherein said characteristic used to modulate said carrier wave is sign.

In Re Patent Application of:
AHMED
Serial No. 10/606,080
Filing Date: June 25, 2003

46. (Previously presented) The apparatus of claim 42, wherein said carrier wave is a radio frequency (RF) signal.

47. (Previously presented) The apparatus of claim 42, wherein said at least one segment is a power amplifier.

48. (Previously presented) The apparatus of claim 42, wherein said at least one segment is a current source.

49-53 (Canceled).